

# Summary of product characteristics for a biocidal product

**Product name:** Visir Oljegrønning Pigmentert

**Product type(s):** PT08 - Wood preservatives (Preservatives)

PT08 - Wood preservatives (Preservatives)

**Authorisation number:** BPD-reg. nr. 734-2

**R4BP 3 asset reference number:** DK-0003196-0000

## Table Of Contents

Administrative information	1
1.1. Trade names of the product	1
1.2. Authorisation holder	1
1.3. Manufacturer(s) of the biocidal products	1
1.4. Manufacturer(s) of the active substance(s)	1
2. Product composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the biocidal product	2
2.2. Type of formulation	2
3. Hazard and precautionary statements	2
4. Authorised use(s)	3
5. General directions for use	7
5.1. Instructions for use	7
5.2. Risk mitigation measures	7
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	7
5.4. Instructions for safe disposal of the product and its packaging	8
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	8
6. Other information	8

## Administrative information

### 1.1. Trade names of the product

Visir Oljegrønning Pigmentert
-------------------------------

### 1.2. Authorisation holder

<b>Name and address of the authorisation holder</b>	Name	Jotun A/S
	Address	P.O.Box 2021 NO-3202 Sandefjord Norway
<b>Authorisation number</b>	BPD-reg. nr. 734-2	
<b>R4BP 3 asset reference number</b>	DK-0003196-0000	
<b>Date of the authorisation</b>	10/04/2012	
<b>Expiry date of the authorisation</b>	28/07/2025	

### 1.3. Manufacturer(s) of the biocidal products

<b>Name of the manufacturer</b>	Jotun AS
<b>Address of the manufacturer</b>	Hystadveien 167 3209 Sandefjord Norway
<b>Location of manufacturing sites</b>	Industriveien 70 3219 Sandefjord Norway

### 1.4. Manufacturer(s) of the active substance(s)

<b>Active substance</b>	51 - tebuconazole
<b>Name of the manufacturer</b>	LANXESS Deutschland GmbH
<b>Address of the manufacturer</b>	Kennedyplatz 1 50569 Cologne Germany
<b>Location of manufacturing sites</b>	Bayer CropScience MO 6412-001 Kansas City United States

## 2. Product composition and formulation

### 2.1. Qualitative and quantitative information on the composition of the biocidal product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
tebuconazole	1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol	Active Substance	107534-96-3	403-640-2	0,6

### 2.2. Type of formulation

AL - Any other liquid
-----------------------

## 3. Hazard and precautionary statements

<b>Hazard statements</b>	<p>Toxic to aquatic life with long lasting effects.</p> <p>Contains 1,2-benzisotiazol-3(2H)-on (BIT) and 3-iod-2-propynyl butylkarbamat (IPBC). May produce an allergic reaction.</p>
<b>Precautionary statements</b>	<p>Keep out of reach of children.</p> <p>Avoid release to the environment.</p> <p>IF ON SKIN:Wash with plenty of soap and water.</p> <p>Dispose of contents to accordingly to local rules..</p>

## 4. Authorised use(s)

### 4.1 Use description

#### Use 1 - Non-professional use

<b>Product type</b>	PT08 - Wood preservatives (Preservatives)
<b>Where relevant, an exact description of the authorised use</b>	Application by brush only. A topcoat has to be applied. The topcoat should be applied within one month after application of Visir Oljegrønning Pigmentert.
<b>Target organism(s) (including development stage)</b>	Scientific name: Basidiomycetes: Common name: Wood rotting basidiomycetes Development stage: Hyphae
<b>Field(s) of use</b>	Outdoor Outdoor use. Use class 3
<b>Application method(s)</b>	Open system: brush treatment - Application method: brush only The primer must be brushed out thoroughly.
<b>Application rate(s) and frequencies</b>	Maximum application rate: 4 m <sup>2</sup> /L (1.53 g tebuconazole /m <sup>2</sup> corresponding to: 0.25 L or 0.255 kg produkt /m <sup>2</sup> ) - 0 - All bare woodwork should have 1 coat of Visir Oljegrønning Pigmentert. All end grains should be saturated (3-4 coats wet on wet).
<b>Category(ies) of users</b>	General public (non-professional)
<b>Pack sizes and packaging material</b>	Can /Tin, Plastic: HDPE , 1L Can /Tin, Plastic: HDPE , 3L Can /Tin, Plastic: HDPE , 10L Can /Tin, Metal: , 1L Can /Tin, Metal: , 3L Can /Tin, Metal: , 10L

#### 4.1.1 Use-specific instructions for use

#### 4.1.1 Use-specific instructions for use

Application method: Brush only.

The product is not to be used for spray application.

The primer must be brushed out thoroughly.

To comply with the efficacy claim, a topcoat has to be applied.

The topcoat should be applied within one month after application.

#### 4.1.2 Use-specific risk mitigation measures

Avoid getting the product on the skin. Wear long-sleeved clothing and use gloves while working with the product.

Not to be used on materials which are in direct contact with food or feeding stuff.

The soil has to be covered during application of the wood preservative product.

The product must not be used near surface water and run-off to surface water has to be prevented.

Not to be used on materials which are in direct contact with water and/or soil.

#### 4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

First aid measures:

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

Emergency measures in case of accidental release to the environment:

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent. Avoid using solvents.

#### 4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

Do not allow to enter drains or watercourses.

European waste catalogue (EWC) code: 08 01 11.

Dispose of this material and its container at hazardous or special waste collection points.

--

#### 4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

Store product in tightly closed original containers, protected against direct sunlight, in a dry, cool and well-ventilated area.  
Shelf life: At least 24 months from date of production.

#### 4.2 Use description

##### Use 2 - Professional use

<b>Product type</b>	PT08 - Wood preservatives (Preservatives)
<b>Where relevant, an exact description of the authorised use</b>	Application by brush only. A topcoat has to be applied. The topcoat should be applied within one month after application of Visir Oljegrønning Pigmentert.
<b>Target organism(s) (including development stage)</b>	Scientific name: Basidiomycetes: Common name: Wood rotting basidiomycetes Development stage: Hyphae
<b>Field(s) of use</b>	Outdoor Outdoor use. Use class 3.
<b>Application method(s)</b>	Open system: brush treatment - Application method: brush only. The primer must be brushed out thoroughly.
<b>Application rate(s) and frequencies</b>	Maximum application rate: 4 m <sup>2</sup> /L (1.53 g tebuconazole /m <sup>2</sup> corresponding to 0.25 L or 0.255 kg produkt /m <sup>2</sup> ) - 0 - All bare woodwork should have 1 coat of Visir Oljegrønning Pigmentert. All end grains should be saturated (3-4 coats wet on wet).
<b>Category(ies) of users</b>	Trained professional Professional
<b>Pack sizes and packaging material</b>	Can /Tin, Plastic: HDPE , 1L Can /Tin, Plastic: HDPE , 3L Can /Tin, Plastic: HDPE , 10L

Can /Tin, Metal: , 1L  
Can /Tin, Metal: , 3L  
Can /Tin, Metal: , 10L

#### 4.2.1 Use-specific instructions for use

Application method: Brush only.

The product is not to be used for spray application.

The primer must be brushed out thoroughly.

To comply with the efficacy claim, a topcoat has to be applied.

The topcoat should be applied within one month after application.

#### 4.2.2 Use-specific risk mitigation measures

Appropriate and suitable PPE (coverall, gloves and goggles) has to be used by professionals.

Not to be used on materials which are in direct contact with food or feeding stuff.

The soil has to be covered during application of the wood preservative product.

The product must not be used near surface water and run-off to surface water has to be prevented.

Not to be used on materials which are in direct contact with water and/or soil.

#### 4.2.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

First aid measures:

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

Emergency measures in case of accidental release to the environment:

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent. Avoid using solvents.



#### **4.2.4 Where specific to the use, the instructions for safe disposal of the product and its packaging**

Do not allow to enter drains or watercourses.

European waste catalogue (EWC) code: 08 01 11.

Dispose of this material and its container at hazardous or special waste collection points.

#### **4.2.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage**

Store product in tightly closed original containers, protected against direct sunlight, in a dry, cool and well-ventilated area.

Shelf life: At least 24 months from date of production.

### **5. General directions for use**

#### **5.1. Instructions for use**

To be applied by brush only.

All bare woodwork should have 1 coat of Visir Oljegrønning Pigmentert.

All end grains should be saturated (3-4 coats wet on wet).

The topcoat should be applied within one month after application of Visir Oljegrønning Pigmentert.

#### **5.2. Risk mitigation measures**

Appropriate and suitable PPE (coverall, gloves and goggles) has to be used by professionals.

The soil has to be covered during application of the wood preservative product.

Not to be used on materials which are in direct contact with food or feeding stuff.

The product must not be used near surface water and run-off to surface water has to be prevented.

Not to be used on materials which are in direct contact with water and/or soil.

#### **5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment**

First aid measures:

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

Emergency measures in case of accidental release to the environment:

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent. Avoid using solvents.

## 5.4. Instructions for safe disposal of the product and its packaging

Do not allow to enter drains or watercourses.

European waste catalogue (EWC) code: 08 01 11.

Dispose of this material and its container at hazardous or special waste collection points.

## 5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

Store product in tightly closed original containers, protected against direct sunlight, in a dry, cool and well-ventilated area.

Shelf life: At least 24 months from date of production.

## 6. Other information

Bilag 1

Oplysninger til etiket og brugsanvisning for Visir Oljegrønning Pigmentert, BPD-reg. nr. 734-2

I. Etiketten skal udformes i overensstemmelse med artikel 69 i biocidforordningen (Forordning (EU) nr. 528/2012), og CLP Forordningen[1].

II. Det er udelukkende ansøgers/godkendelsesindehaverens ansvar, at etiket, mærkning og pakning lever op til lovens krav, jf. biocidforordningen artikel 69. Nedstående tekst i afsnit III er bidrag til overholdelsen af reglerne og således kun en del af de krav, som stilles til blandt andet etiketten.

III. Etiketten skal indeholde nedenstående oplysninger. Oplysninger i citationstegn skal angives ordret:

1) I hovedfeltet:  
"Træbeskyttelsesmiddel

Må kun anvendes over jord til træbeskyttelse mod træødelæggende svamp. Må kun anvendes i brugsklasse 3 jf. DS/EN335-1."

2) I advarselsfeltet:

**"FORSIGTIG**

Giftig for vandlevende organismer, med langvarige virkninger (H411).

Undgå udledning til miljøet

Udslip opsamles

Vask huden efter arbejdet.

Overtrædelse af nedenstående særligt fremhævede forskrifter kan medføre straf:

**Må kun anvendes over jord til træbeskyttelse mod trædelæggende svamp. Må kun anvendes i brugsklasse 3 jf. DS/EN335-1.**

**Må kun anvendes i doseringer på 125-250 ml/m<sup>2</sup> ved pensling.**

**Må ikke anvendes mod andre skadevoldere og ikke i højere doseringer end de i brugsanvisningen nævnte.**

**Må ikke anvendes til træværk, der kommer i direkte berøring med fødevarer og foderstoffer.**

**Må ikke anvendes indendørs.**

**For at beskytte organismer, der lever i vand, må produktet og det behandlede træ ikke anvendes i umiddelbar nærhed af vandmiljøet (vandløb, søer m.v.).**

**Det behandlede træ skal overfladebehandles med for eksempel en maling. Overfladebehandlingen skal løbende vedligeholdes.**

**Ved påførsel skal jorden afdækkes, således at eventuelt spild opsamles.**

**Må ikke tømmes i kloakfløb.**

**Opbevares utilgængeligt for børn.**

**Må ikke opbevares sammen med fødevarer, drikkevarer og foderstoffer.**

Nedenstående supplerende forskrifter er kun relevant ved erhvervsmæssig anvendelse:

For at beskytte organismer, der lever i vand, må det behandlede træ ikke anvendes i eller i umiddelbar nærhed af vandmiljøet (vandløb, søer m.v.).

Det behandlede træ skal overfladebehandles med for eksempel en maling. Overfladebehandlingen skal løbende vedligeholdes.

**Ovenstående indrammede angivelse skal være tydeligt anført på et faktaark eller lignende, der følger det behandlede træ. ”**

Farepiktogram: GHS09

Evt. oplysninger om førstehjælp.

3) I deklaraionsfeltet:

a) Teksten "Træbeskyttelsesmiddel BPD-nr. 734-2. Aktivstoffet er godkendt efter biociddirektivet (98/8/EF). Midlet er godkendt efter Miljøministeriets bekendtgørelse om bekæmpelsesmidler".

b) Oplysning om præparattype: "Væske" for dette præparat.

c) Indholdet af aktivstof i vægtprocent (% w/w) og g/L ved 20 °C.

d) Sætningen: "Indeholder 3-iodo-propyryl butylcarbamate (IPBC) og 1,2-benzisothiazol-3(2H)-one (BIT). Kan udløse allergisk reaktion".

e) Udløbsdatoen skal anføres. Denne dato må højst være to år efter produktionsdatoen. Etikettens dato kan udformes som en hen-visning til en produktionsdato andetsteds på emballagen.

f) Batchnummer eller – betegnelse skal anføres.

g) Pakningsstørrelse i liter.

h) Godkendelsesindehavers navn og adresse.

4) Brugsanvisningen:

Oplysninger om skadevoldere, anvendelsesområde og doseringer.

Følgende retningslinjer gælder i forhold til bortskaffelse.

Der skal mærkes med sikkerhedssætning P501: "Indholdet/holderen bortskaffes i overensstemmelse med kommunale regler for affaldshåndtering."

Derudover skal mærkningen ske efter følgende retningslinjer:

Rester skal afleveres til den kommunale affaldsordning for farligt affald.

Tomme beholdere kan bortskaffes med dagrenovationen.