## Summary of product characteristics for a biocidal product

Product name: Vivexyl Plus Teak 504

Product type(s):	PT08 - Wood preservatives (Preservatives)
	PT08 - Wood preservatives (Preservatives)

R4BP 3 asset reference number: BG-0014791-0023

### **Table Of Contents**

Administrative information	1
1.1. Trade names of the product	1
1.2. Authorisation holder	1
1.3. Manufacturer(s) of the biocidal products	1
1.4. Manufacturer(s) of the active substance(s)	2
2. Product composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the biocidal product	2
2.2. Type of formulation	3
3. Hazard and precautionary statements	3
4. Authorised use(s)	4
5. General directions for use	34
5.1. Instructions for use	34
5.2. Risk mitigation measures	35
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	36
5.4. Instructions for safe disposal of the product and its packaging	39
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	41
6. Other information	43

### 1.1. Trade names of the product

Vivexyl Plus Teak 504		
Vivexyl Plus Teak 504		
Vivexyl Plus Teak 504		

### 1.2. Authorisation holder

r

Name and address of the	Name Akzo Nobel Decorative Coatings B.V.	
authorisation holder	Address	Christian Neefestraat 2 - Attn. Director PSRAQ 1077 WW Amsterdam Netherlands
Authorisation number	2248-2 1-1	
R4BP 3 asset reference number	BG-0014791-0023	

Date of the authorisation

Expiry date of the authorisation

BG-0014791-0023
22/06/2015
31/07/2025

#### 1.3. Manufacturer(s) of the biocidal products

Г

Address of the manufacturer

Location of manufacturing sites

Akzo Nobel Decorative Paints
Z.I. "Les Bas Prés", C.S. 70113 60160 Montataire France
Z.I. "Les Bas Prés", C.S. 70113 60160 Montataire France

٦

\_

Active substance	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
Name of the manufacturer	TROY Corporation
Address of the manufacturer	8 Vreeland Road, Florham Park 07932 New Jersey United States
Location of manufacturing sites	One Avenue L NJ 07105 Newark United States
Active substance	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
Name of the manufacturer	TROY Chemical Corporation
Address of the manufacturer	One Avenue L NJ 07105 Newark United States
Location of manufacturing sites	12e Uiverlaan 3145 Maassluis Netherlands

## 2. Product composition and formulation

## 2.1. Qualitative and quantitative information on the composition of the biocidal product

IUPAC name	Function	CAS number	EC number	Content (%)
	Active Substance	55406-53-6	259-627-5	0,7
	Non-active substance	64742-47-8		22,222
	Non-active substance	96-29-7		0,388
Alkyd solution	Non-active substance			35,86
	Non-active substance	8001-26-1		2,5
	Non-active substance	68953-58-2		0,571
	Non-active substance	8002-43-5		0,057
		Active Substance   Non-active   Substance   Non-active   Substance   Alkyd solution   Non-active   Non-active   Substance   Non-active   Substance   Non-active   Substance   Non-active   Substance   Non-active   Substance   Non-active   Substance   Non-active   Non-active   Substance	Active Substance55406-53-6Non-active substance64742-47-8Non-active substance96-29-7Alkyd solutionNon-active substanceNon-active substance8001-26-1Non-active substance68953-58-2Non-active substance8002-43-5	Active Substance55406-53-6259-627-5Non-active substance64742-47-8

Calcium preparation	Non-active substance	68551-41-7	1,99
Zirconium preparation	Non-active substance	22464-99-9	1,994
Manganese preparation	Non-active substance	15956-58-8	0,1
silicon-free polymer	Non-active substance	64741-65-7	0,2
methylen diaminomethyl polycondensate	Non-active substance	9011-05-6	1,5
magnesium sulphate heptahydrat	Non-active substance	10034-99-8	0,14
component of polyphase AF3	Non-active substance		1,633
water	Non-active substance	7732-18-5	28,02
substance of the hydrolyphenyl- benzotriazole	Non-active substance	127519-17-9	0,2
decanediodic acid	Non-active substance	129757-67-1	0,1
1,4,7 trimethyl-1,4,7 osv	Non-active substance	96556-05-7	0,67
Cl pigment carbon black 7	Non-active substance	1333-86-4	0,113
CI pigment red 101	Non-active substance	1309-37-1	0,488
CI pigment yellow 42	Non-active substance	20344-49-4	0,555
CI pigment white 6	Non-active substance	13463-67-7	0
CI pigment blue 15:4	Non-active substance	147-14-8	0
CI pigment red 122	Non-active substance	980-26-7	0
CI pigment green 7	Non-active substance	1328-53-6	0
C.I. pigment violet 23	Non-active substance	6358-30-1	0

## 2.2. Type of formulation

AL - Any other liquid

## 3. Hazard and precautionary statements

Hazard statements

	Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime. May produce an allergic reaction.
Precautionary statements	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Avoid release to the environment. Call a POISON CENTER if you feel unwell. Dispose of contents to local rules. Call a POISON CENTER if you feel unwell. Dispose of container to local rules.

## 4. Authorised use(s)

### 4.1 Use description

### Use 1 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	For all outside wood, which is not I direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.
Target organism(s) (including development stage)	Scientific name: Aureobasidium pullulans spp. Common name: Sapstain fungi Development stage:
	Indees
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description:
	Not available

Application rate(s) and frequencies	Application Rate: 200-250 ml/m <sup>2</sup> Dilution (%): No dilution Number and timing of application: 200-250 g/m <sup>2</sup>
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	Can /Tin, Metal: , 0.75L - 20L (0.75L; 1L; 2.5L; 3L; 5L; 5.5L; 6L; 9L; 9.5L; 10L; 11L; 11.5L; 12L; 20L)

### 4.1.1 Use-specific instructions for use

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.

#### 4.1.2 Use-specific risk mitigation measures

Keep out of reach of children. Wear suitable protective clothing and gloves

## 4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.

If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

## 4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

European waste code (EWC): 03 02 05: other wood preservatives containing dangerous substances / 20 01 27: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

# 4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

Store product in tightly closed original containers at temperatures about 5 - 30°C. The product is stable for 3 years at room temperature.

### 4.2 Use description

### Use 2 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

### 4.2.1 Use-specific instructions for use

see other section

### 4.2.2 Use-specific risk mitigation measures

see other section

4.2.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.2.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.2.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.3 Use description

#### Use 3 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description:

	Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

### 4.3.1 Use-specific instructions for use

see other section

### 4.3.2 Use-specific risk mitigation measures

see other section

**4.3.3** Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.3.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## **4.3.5** Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

### 4.4 Use description

## Use 4 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

## 4.4.1 Use-specific instructions for use

see other section

### 4.4.2 Use-specific risk mitigation measures

## 4.4.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

# 4.4.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.4.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.5 Use description

#### Use 5 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor
Field(s) of use	Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2

Category(ies) of users

#### Professional

General public (non-professional)

Pack sizes and packaging material

can, not available , 1

1-20L

### 4.5.1 Use-specific instructions for use

see other section

### 4.5.2 Use-specific risk mitigation measures

see other section

## 4.5.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.5.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.5.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.6 Use description

#### Use 6 - Against wood discolouring fungi

Product type

PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor
	Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional
	General public (non-professional)
Pack sizes and packaging material	can, not available , 1
	1-20L

## 4.6.1 Use-specific instructions for use

see other section

### 4.6.2 Use-specific risk mitigation measures

see other section

4.6.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

## 4.6.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.6.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

### 4.7 Use description

### Use 7 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1

1-20L

## 4.7.1 Use-specific instructions for use

see other section

## 4.7.2 Use-specific risk mitigation measures

see other section

4.7.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

# 4.7.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

# 4.7.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

### 4.8 Use description

Use 8 - Against wood discolouring fungi

### Product type

PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised use

Target organism(s) (including development stage)

Scientific name: Common name: wood discolouring fungi Development stage: Not available

Not available

Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

### 4.8.1 Use-specific instructions for use

see other section
-------------------

### 4.8.2 Use-specific risk mitigation measures

see other section

Г

## 4.8.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.8.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

# 4.8.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

### 4.9 Use description

### Use 9 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

### 4.9.1 Use-specific instructions for use

see other section

### 4.9.2 Use-specific risk mitigation measures

see other section

4.9.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.9.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.9.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.10 Use description

#### Use 10 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description:

	Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

### 4.10.1 Use-specific instructions for use

see other section

### 4.10.2 Use-specific risk mitigation measures

see other section

**4.10.3** Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.10.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.10.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

### 4.11 Use description

## Use 11 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

## 4.11.1 Use-specific instructions for use

see other section

### 4.11.2 Use-specific risk mitigation measures

## 4.11.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.11.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.11.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.12 Use description

#### Use 12 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor
	Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and	Application Rate: 200-250 ml/m2
frequencies	Dilution (%): 0 Number and timing of application: 200-250 g/m2

Category(ies) of users

#### Professional

General public (non-professional)

Pack sizes and packaging material

can, not available , 1

1-20L

### 4.12.1 Use-specific instructions for use

see other section

### 4.12.2 Use-specific risk mitigation measures

see other section

## **4.12.3** Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.12.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.12.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.13 Use description

#### Use 13 - Against wood discolouring fungi

Product type

PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor
	Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional
	General public (non-professional)
Pack sizes and packaging material	can, not available , 1
	1-20L

### 4.13.1 Use-specific instructions for use

see other section

### 4.13.2 Use-specific risk mitigation measures

see other section

4.13.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

# 4.13.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.13.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

### 4.14 Use description

### Use 14 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1

1-20L

## 4.14.1 Use-specific instructions for use

see other section

### 4.14.2 Use-specific risk mitigation measures

see other section

4.14.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

4.14.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.14.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.15 Use description

Use 15 - Against wood discolouring fungi

#### Product type

PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised use

Target organism(s) (including development stage)

Scientific name: Common name: wood discolouring fungi Development stage: Not available

Not available

Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

### 4.15.1 Use-specific instructions for use

see	other	section	

### 4.15.2 Use-specific risk mitigation measures

see other section

## 4.15.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.15.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.15.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

### 4.16 Use description

### Use 16 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

### 4.16.1 Use-specific instructions for use

see other section

### 4.16.2 Use-specific risk mitigation measures

see other section

4.16.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.16.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.16.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.17 Use description

#### Use 17 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description:

	Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

### 4.17.1 Use-specific instructions for use

see other section

### 4.17.2 Use-specific risk mitigation measures

see other section

4.17.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.17.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.17.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

### 4.18 Use description

## Use 18 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

## 4.18.1 Use-specific instructions for use

see other section

## 4.18.2 Use-specific risk mitigation measures

## 4.18.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.18.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.18.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.19 Use description

#### Use 19 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor
	Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and	Application Rate: 200-250 ml/m2
frequencies	Dilution (%): 0 Number and timing of application: 200-250 g/m2

Category(ies) of users

#### Professional

General public (non-professional)

Pack sizes and packaging material

can, not available , 1

1-20L

### 4.19.1 Use-specific instructions for use

see other section

### 4.19.2 Use-specific risk mitigation measures

see other section

## 4.19.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

## 4.19.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.19.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

#### 4.20 Use description

#### Use 20 - Against wood discolouring fungi

Product type

PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised use	Not available	
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	
Field(s) of use	Indoor	
	Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description: Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	
Category(ies) of users	Professional	
	General public (non-professional)	
Pack sizes and packaging material	can, not available , 1	
	1-20L	

## 4.20.1 Use-specific instructions for use

see other section

### 4.20.2 Use-specific risk mitigation measures

see other section

4.20.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

## 4.20.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

## 4.20.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

### 4.21 Use description

### Use 21 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1

1-20L

# 4.21.1 Use-specific instructions for use

see other section

# 4.21.2 Use-specific risk mitigation measures

see other section

**4.21.3** Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section

4.21.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

see other section

4.21.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section

# 5. General directions for use

# 5.1. Instructions for use

#### Sikkens Cetol HLS plus(BP)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Hazel) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Boxwood) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Blue) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Ebony) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Teak) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Dark Oak) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Pine) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Oregon) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Colourless) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Olive Green) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Cedar) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use, Sikkens Cetol HLS plus (BP) (Fir green) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Mahogany) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Chestnut) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Light Oak) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Old Pine) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Larch) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Rosewood) For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use. Sikkens Cetol HLS plus (BP) (Russian Green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

## **5.2.** Risk mitigation measures

## Sikkens Cetol HLS plus(BP)

Keep out of reach of children. Wear suitable protective clothing and gloves.
Sildene Catel LILS plue (PD) (Llezel)
Sikkens Cetol HLS plus (BP) (Hazel) Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Boxwood)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Blue)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Ebony)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Teak)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Dark Oak)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Pine)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Oregon)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Colourless)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Olive Green)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Cedar) Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Fir green)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Mahogany)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Chestnut)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Light Oak)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Old Pine)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Larch)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Rosewood)
Keep out of reach of children. Wear suitable protective clothing and gloves.
Sikkens Cetol HLS plus (BP) (Russian Green)
Keep out of reach of children. Wear suitable protective clothing and gloves.

# **5.3.** Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.

If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Hazel)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Boxwood)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Blue)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Ebony)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately. Sikkens Cetol HLS plus (BP) (Teak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately. Sikkens Cetol HLS plus (BP) (Dark Oak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce

vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Pine)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### Sikkens Cetol HLS plus (BP) (Oregon)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Colourless)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Olive Green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Cedar)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Fir green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Mahogany)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Chestnut)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately. Sikkens Cetol HLS plus (BP) (Light Oak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Old Pine)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eves: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately. Sikkens Cetol HLS plus (BP) (Larch)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eves: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Rosewood)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Russian Green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately

## 5.4. Instructions for safe disposal of the product and its packaging

European waste code (EWC): 03 02 05: other wood preservatives containing dangerous substances / 20 01 27: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Hazel)

European waste code (EWĆ): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Boxwood)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Blue)

European waste code (EWĆ): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

## Sikkens Cetol HLS plus (BP) (Ebony)

European waste code (EWĆ): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Teak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP)

European waste code (EWĆ): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Dark Oak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Pine)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Oregon)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Colourless)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Olive Green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Cedar)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Fir green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Mahogany)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

## Sikkens Cetol HLS plus (BP) (Chestnut)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Light Oak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Old Pine)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Larch)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Rosewood)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

#### Sikkens Cetol HLS plus (BP) (Russian Green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

## 5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

Sikkens Cetol HLS plus(BP)

Store product in tightly closed original containers at temperatures about 5 - 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Hazel)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Boxwood)

Store product in tightly closed original containers at temperatures about  $5 - 30^{\circ}$ C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Blue)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Ebony)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Teak)

Store product in tightly closed original containers at temperatures about  $5 - 30^{\circ}$ C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Dark Oak)

Store product in tightly closed original containers at temperatures about  $5 - 30^{\circ}$ C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Pine)

Store product in tightly closed original containers at temperatures about  $5 - 30^{\circ}$ C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Oregon)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Colourless)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Olive Green)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Cedar)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Fir green)

Store product in tightly closed original containers at temperatures about  $5 - 30^{\circ}$ C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Mahogany)

Store product in tightly closed original containers at temperatures about  $5 - 30^{\circ}$ C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Chestnut)

Store product in tightly closed original containers at temperatures about  $5 - 30^{\circ}$ C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Light Oak)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Old Pine)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature. Sikkens Cetol HLS plus (BP) (Larch)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Russian Green)

Store product in tightly closed original containers at temperatures about  $5 - 30^{\circ}$ C. The product is stable for 3 years at room temperature.

# 6. Other information

Sikkens Cetol HLS plus(BP), DK Sikkens Cetol HLS plus(BPR), IT Sikkens Cetol HLS plus(BPR), CH Xyladecor Holzschutzlasur BPR. AT Xyladecor Classic HP(BPR), CZ Xyladecor Classic HP(BPR), SK Vivexyl Plus, GR SADOLIN Classic HP(BPR), HU SADOLIN Classic HP(BPR), PL SADOLIN IMPREGNAT CLASSIC HP(BPR), PL SADOLIN Classic(BPR), PL SADOLIN IMPREGNAT CLASSIC(BPR), PL Vivexyl Plus, CY Vivexyl Plus, BG Sikkens Cetol HLS plus(BP) Use biocides safely. Always read the label and product information before use. P501: Dispose of container to local rules Sikkens Cetol HLS plus (BP) (Hazel) Use biocides safely. Always read the label and product information before use. Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime." Sikkens Cetol HLS plus (BP) (Boxwood) Use biocides safely. Always read the label and product information before use. Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime." Sikkens Cetol HLS plus (BP) (Blue) Use biocides safely. Always read the label and product information before use. Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime." Sikkens Cetol HLS plus (BP) (Ebony) Use biocides safely. Always read the label and product information before use. Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime." Sikkens Cetol HLS plus (BP) (Teak) Use biocides safely. Always read the label and product information before use. Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime." Sikkens Cetol HLS plus (BP) Use biocides safely. Always read the label and product information before use. Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime." Sikkens Cetol HLS plus (BP) (Dark Oak) Use biocides safely. Always read the label and product information before use. Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime." Sikkens Cetol HLS plus (BP) (Pine) Use biocides safely. Always read the label and product information before use. Suplementary statemet under Labelling:• "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime." Sikkens Cetol HLS plus (BP) (Oregon)

	Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Colourless) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Olive Green) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Cedar) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Fir green) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Mahogany) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Chestnut) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Light Oak) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Old Pine) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Larch) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Rosewood) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Sikkens Cetol HLS plus (BP) (Russian Green) Use biocides safely. Always read the label and product information before use.
	Suplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."
	Bilag 1 Oplysninger til etiket og brugsanvisning for Sikkens Cetol HLS Plus (BP), BPR-reg. nr. 782-7 Rettelse: Tilføjet H412 til bilag 1.
	I. Etiketten skal udformes i overensstemmelse med artikel 69 i biocidforordningen (Forordning (EU) nr. 528/2012), og CLP Forordningen1.
	II. Det er udelukkende ansøgers/godkendelsesindehaverens ansvar, at etiket, mærkning og pakning lever op til lovens krav, jf. biocidforordningen artikel 69. Nedstående tekst i afsnit III er bidrag til overholdelsen af reglerne og således kun en del af de krav, som stilles til blandt andet etiketten.
	<ul><li>III. Etiketten skal indeholde nedenstående oplysninger. Oplysninger i citationstegn skal angives ordret:</li><li>1) I hovedfeltet:</li></ul>
	"Træbeskyttelsesmiddel (PT8) Må kun anvendes over jord som træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1." 2) I advarselsfeltet:
	" FORSIGTIG Skadelig for vandlevendeorganismer, medlangvarige virkninger (H412)
	Undgå udledning til miljøet (P273) Vær opmærksom på, at Arbejdstilsynet har regler for arbejde med bekæmpelsesmidler. Læs nærmere i det eventuelt lovpligtige sikkerhedsdatablad samt i Arbejdstilsynets informationsmateriale om bekæmpelsesmidler.
1	

Vask huden efter arbeide. 1 Europa-Parlamentets og Rådets forordning (EF) Nr. 1272/2008 af 16. december 2008 om klassificering, mærkning og emballering af stoffer og blandinger og om ændring og ophævelse af direktiv 67/548/EØF og 1999/45/EF og om ændring af forordning (EF) nr. 1907/2006 Overtrædelse af nedenstående særligt fremhævede forskrifter kan medføre straf: Må kun anvendes over jord som træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1. Må kun anvendes i doseringer på 200-250 ml/m2 ved pensling. Må ikke anvendes mod andre skadevoldere og ikke i højere doseringer end de i brugsanvisningen nævnte. Må ikke anvendes indendørs. Må ikke anvendes til træværk, der kommer i direkte berøring med fødevarer og foderstoffer. Opbevares utilgængeligt for børn. Må ikke opbevares sammen med fødevarer, drikkevarer og foderstoffer. Evt. oplysninger om førstehjælp. 3) I deklarationsfeltet: a) Teksten "Træbeskyttelsesmiddel BPR-reg. nr. 782-7. Aktivstof og biocidholdigt produkt er godkendt efter biocidforordningen (Forordning (EU) nr. 528/2012)". b) Oplysning om præparattype: "væske" for dette præparat. c) Indholdet af aktivstof i vægtprocent og g/L ved 20 °C d) Sætningen: "Indeholder IPBC og 2-butanonoxim. Kan udløse allergisk reaktion" e) Udløbsdatoen skal anføres. Denne dato må højst være 3 år efter produktionsdatoen. Etikettens dato kan udformes som en henvisning til en produktionsdato andetsteds på emballagen. f) Batchnummer eller – betegnelse skal anføres. g) Pakningsstørrelse i liter. h) Navn og firmaadresse, herunder telefonnummer, for en i en medlemsstat etableret fysisk eller juridisk person, som er ansvarlig for markedsføringen (godkendelsesindehaveren). 4) Brugsanvisningen: Óplysninger om skadevoldere, anvendelsesområde og doseringer. Følgende retningslinjer gælder i forhold til bortskaffelse. Der skal mærkes med sikkerhedssætning P501: "Indholdet/beholderen bortskaffes i overensstemmelse med kommunale regler for affaldshåndtering." Derudover skal mærkningen ske efter følgende retningslinjer: Tom emballage og rester bortskaffes i henhold til kommunale retningslinjer.