

**EN**

***ANNEX***

**SUMMARY OF PRODUCT CHARACTERISTICS FOR A BIOCIDAL PRODUCT**

Sikkens Cetol HLS plus (BP) (Olive Green)

**Product type(s)**

PT08: Wood preservatives

**Authorisation number:** 782-2 1-1

**R4BP asset number:** DK-0012313-0011

---

1. ADMINISTRATIVE INFORMATION .....	3
1.1. Trade name(s) of the product .....	3
1.2. Authorisation holder .....	3
1.3. Manufacturer(s) of the product .....	3
1.4. Manufacturer(s) of the active substance(s) .....	3
2. PRODUCT COMPOSITION AND FORMULATION .....	4
2.1. Qualitative and quantitative information on the composition of the product .....	4
2.2. Type(s) of formulation .....	4
3. HAZARD AND PRECAUTIONARY STATEMENTS .....	5
4. AUTHORISED USE(S) .....	6
4.1. Use description .....	6
5. GENERAL DIRECTIONS FOR USE .....	8
5.1. Instructions for use .....	8
5.2. Risk mitigation measures .....	9
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment .....	10
5.4. Instructions for safe disposal of the product and its packaging .....	13
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage .....	14
6. OTHER INFORMATION .....	17

## 1. ADMINISTRATIVE INFORMATION

### 1.1. Trade name(s) of the product

Trade name(s)	Sikkens Cetol HLS plus(BP) Olive Green SADOLIN IMPREGNAT CLASSIC HP + Akacja SADOLIN IMPREGNAT CLASSIC + Akacja SADOLIN CLASSIC HP + Akacja SADOLIN CLASSIC + Akacja
---------------	--

### 1.2. Authorisation holder

Name and address of the authorisation holder	Name	Akzo Nobel Decorative Coatings B.V.
	Address	Christian Neefstraat 2 - Attn. Director PSRAQ 1077 WW Amsterdam Netherlands
Authorisation number		782-2 1-1
<i>R4BP asset number</i>		DK-0012313-0011
Date of the authorisation		22/06/2015
Expiry date of the authorisation		30/10/2025

### 1.3. Manufacturer(s) of the product

Name of manufacturer	Akzo Nobel Decorative Paints
Address of manufacturer	Z.I. "Les Bas Prés", C.S. 70113 60160 Montataire France
Location of manufacturing sites	Z.I. "Les Bas Prés", C.S. 70113 60160 Montataire France

### 1.4. Manufacturer(s) of the active substance(s)

Active substance	3-iodo-2-propynylbutylcarbamate (IPBC)
Name of manufacturer	TROY Corporation
Address of manufacturer	8 Vreeland Road, Florham Park 07932 New Jersey United States (the)
Location of manufacturing sites	One Avenue L NJ 07105 Newark United States (the)

Active substance	3-iodo-2-propynylbutylcarbamate (IPBC)
Name of manufacturer	TROY Chemical Corporation
Address of manufacturer	One Avenue L NJ 07105 Newark United States (the)
Location of manufacturing sites	12e Uiverlaan 3145 Maassluis Netherlands (the)

---

## 2. PRODUCT COMPOSITION AND FORMULATION

### 2.1. Qualitative and quantitative information on the composition of the product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		active substance	55406-53-6	259-627-5	0,7

### 2.2. Type(s) of formulation

AL Any other liquid

---

### 3. HAZARD AND PRECAUTIONARY STATEMENTS

Hazard statements	H412: Harmful to aquatic life with long lasting effects.  EUH066: Repeated exposure may cause skin dryness or cracking.  EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
Precautionary statements	P101: If medical advice is needed, have product container or label at hand.  P102: Keep out of reach of children.  P262: Do not get in eyes, on skin, or on clothing.  P273: Avoid release to the environment.  P312: Call a POISON CENTER if you feel unwell.  P501: Dispose of contents to local rules.  P501: Dispose of container to local rules.

## 4. AUTHORISED USE(S)

### 4.1. Use description

**Table 1. Against wood discolouring fungi**

Product type	PT08: Wood preservatives
Where relevant, an exact description of the authorised use	For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.
Target organism(s) (including development stage)	Scientific name: Aureobasidium pullulans spp. Common name: sapstain fungi Development stage: no data
Field(s) of use	indoor use outdoor use
Application method(s)	Method: open system: brush treatment  Detailed description: Not available
Application rate(s) and frequency	Application Rate: 200-250 ml/m <sup>2</sup>  Dilution (%): No dilution  Number and timing of application: 200-250 g/m <sup>2</sup>
Category(ies) of users	professional ; general public (non-professional)
Pack sizes and packaging material	Can /Tin, Metal: , 0.75L - 20L (0.75L; 1L; 2.5L; 3L; 5L; 5.5L; 6L; 9L; 9.5L; 10L; 11L; 11.5L; 12L; 20L)

#### 4.1.1. Use-specific instructions for use

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.

#### 4.1.2. Use-specific risk mitigation measures

Keep out of reach of children. Wear suitable protective clothing and gloves

#### 4.1.3. Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.

If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### 4.1.4. Where specific to the use, the instructions for safe disposal of the product and its packaging

European waste code (EWC): 03 02 05: other wood preservatives containing dangerous substances / 20 01 27: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

---

**4.1.5. Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage**

Store product in tightly closed original containers at temperatures about 5 - 30°C. The product is stable for 3 years at room temperature.

---

## 5. GENERAL DIRECTIONS FOR USE<sup>1</sup>

### 5.1. Instructions for use

Sikkens Cetol HLS plus(BP)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Hazel)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Boxwood)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Blue)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Ebony)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Teak)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Dark Oak)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Pine)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Oregon)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Colourless)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Olive Green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Cedar)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Fir green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Mahogany)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Chestnut)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Light Oak)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Old Pine)

---

<sup>1</sup>Instructions for use, risk mitigation measures and other directions for use under this section are valid for any authorised uses.



---

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Larch)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Rosewood)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Russian Green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

## **5.2. Risk mitigation measures**

Sikkens Cetol HLS plus(BP)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Hazel)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Boxwood)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Blue)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Ebony)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Teak)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Dark Oak)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Pine)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Oregon)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Colourless)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Olive Green)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Cedar)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Fir green)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Mahogany)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Chestnut)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Light Oak)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Old Pine)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Larch)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Rosewood)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Russian Green)

Keep out of reach of children. Wear suitable protective clothing and gloves.

---

### **5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment**

#### **Sikkens Cetol HLS plus(BP)**

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.

If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### **Sikkens Cetol HLS plus (BP) (Hazel)**

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### **Sikkens Cetol HLS plus (BP) (Boxwood)**

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### **Sikkens Cetol HLS plus (BP) (Blue)**

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### **Sikkens Cetol HLS plus (BP) (Ebony)**

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### **Sikkens Cetol HLS plus (BP) (Teak)**

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### **Sikkens Cetol HLS plus (BP)**

---

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Dark Oak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Pine)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Oregon)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Colourless)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Olive Green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Cedar)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

---

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Fir green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Mahogany)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Chestnut)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Light Oak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Old Pine)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Larch)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

---

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Rosewood)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If

swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Russian Green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If

swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### **5.4. Instructions for safe disposal of the product and its packaging**

Sikkens Cetol HLS plus(BP)

European waste code (EWC): 03 02 05: other wood preservatives containing dangerous substances / 20 01 27: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Hazel)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Boxwood)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Blue)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Ebony)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Teak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Dark Oak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Pine)

---

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Oregon)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Colourless)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Olive Green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Cedar)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Fir green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Mahogany)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Chestnut)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Light Oak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Old Pine)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Larch)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Rosewood)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Russian Green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

## **5.5. Conditions of storage and shelf-life of the product under normal conditions of storage**

Sikkens Cetol HLS plus(BP)

Store product in tightly closed original containers at temperatures about 5 - 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Hazel)

---

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Boxwood)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Blue)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Ebony)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Teak)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Dark Oak)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Pine)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Oregon)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Colourless)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Olive Green)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Cedar)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Fir green)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Mahogany)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Chestnut)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Light Oak)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Old Pine)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Larch)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Rosewood)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Russian Green)

---

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.



---

## 6. OTHER INFORMATION

Sikkens Cetol HLS plus(BP), DK  
Sikkens Cetol HLS plus(BPR), IT  
Sikkens Cetol HLS plus(BPR), CH  
Xyladecor Holzschutzlasur BPR, AT  
Xyladecor Classic HP(BPR), CZ  
Xyladecor Classic HP(BPR), SK  
Vivexyl Plus, GR  
SADOLIN Classic HP(BPR), HU  
SADOLIN Classic HP(BPR), PL  
SADOLIN IMPREGNAT CLASSIC HP(BPR), PL  
SADOLIN Classic(BPR), PL  
SADOLIN IMPREGNAT CLASSIC(BPR), PL  
Vivexyl Plus, CY  
Vivexyl Plus, BG  
Sikkens Cetol HLS plus(BP)

Use biocides safely. Always read the label and product information before use.  
P501: Dispose of container to local rules

Sikkens Cetol HLS plus (BP) (Hazel)  
Use biocides safely. Always read the label and product information before use.

Supplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate."  
Sikkens Cetol HLS plus (BP) (Boxwood)  
Use biocides safely. Always read the label and product information before use.

Supplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"  
Sikkens Cetol HLS plus (BP) (Blue)  
Use biocides safely. Always read the label and product information before use.

Supplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"  
Sikkens Cetol HLS plus (BP) (Ebony)  
Use biocides safely. Always read the label and product information before use.

Supplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"  
Sikkens Cetol HLS plus (BP) (Teak)  
Use biocides safely. Always read the label and product information before use.

Supplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"  
Sikkens Cetol HLS plus (BP)  
Use biocides safely. Always read the label and product information before use.

Supplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"  
Sikkens Cetol HLS plus (BP) (Dark Oak)  
Use biocides safely. Always read the label and product information before use.

Supplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate."  
Sikkens Cetol HLS plus (BP) (Pine)  
Use biocides safely. Always read the label and product information before use.

Supplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate."  
Sikkens Cetol HLS plus (BP) (Oregon)  
Use biocides safely. Always read the label and product information before use.

Supplementary statemet under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

---

Sikkens Cetol HLS plus (BP) (Colourless)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Sikkens Cetol HLS plus (BP) (Olive Green)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Sikkens Cetol HLS plus (BP) (Cedar)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Sikkens Cetol HLS plus (BP) (Fir green)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Sikkens Cetol HLS plus (BP) (Mahogany)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate."

Sikkens Cetol HLS plus (BP) (Chestnut)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Sikkens Cetol HLS plus (BP) (Light Oak)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Sikkens Cetol HLS plus (BP) (Old Pine)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Sikkens Cetol HLS plus (BP) (Larch)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Sikkens Cetol HLS plus (BP) (Rosewood)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Sikkens Cetol HLS plus (BP) (Russian Green)

Use biocides safely. Always read the label and product information before use.

Supplementary statement under Labelling:•"Contains 3-iodo-2-propynyl butylcarbamate"

Bilag 1 Oplysninger til etiket og brugsanvisning for Sikkens Cetol HLS plus Reg. Nr.: 782-7

I. Etiketten skal udformes i overensstemmelse med artikel 69 i biocidforordningen (Forordning (EU) nr. 528/2012), og CLP Forordningen[1].

II. Det er udelukkende ansøgers/godkendelsesindehaverens ansvar, at etiket, mærkning og pakning lever op til lovens krav, jf. biocidforordningen artikel 69.

Nedstående tekst i afsnit III er bidrag til overholdelsen af reglerne og således kun en del af de krav, som stilles til blandt andet etiketten.

III. Etiketten skal indeholde nedenstående oplysninger. Oplysninger i citationstegn skal angives ordret:

1) I hovedfeltet:

”Træbeskyttelsesmiddel (PT8)

Må kun anvendes over jord til træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1.”

2) I advarselsfeltet:

” **FORSIGTIG** ”

---

Skadelig for vandlevende organismer, med langvarige virkninger (H412).

Undgå udledning til miljøet (P273).

Vask huden efter arbejdet.

Vær opmærksom på, at Arbejdstilsynet har regler for arbejde med bekæmpelsesmidler. Læs nærmere i det eventuelt lovpligtige sikkerhedsdatablad samt i Arbejdstilsynets informationsmateriale om bekæmpelsesmidler.

Overtrædelse af nedenstående særligt fremhævede forskrifter kan medføre straf:

**Må kun anvendes til træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1.**

**Må kun anvendes i doseringer på 160-200 ml/m<sup>2</sup> ved pensling.**

**Må ikke anvendes mod andre skadevoldere og ikke i højere doseringer end de i brugsanvisningen nævnte.**

**Må ikke anvendes til træværk, der kommer i direkte berøring med fødevarer og foderstoffer.**

**Må ikke anvendes indendørs.**

**Må ikke tømmes i kloakfløb.**

**Opbevares utilgængeligt for børn.**

**Må ikke opbevares sammen med fødevarer, drikkevarer og foderstoffer.”**

Evt. oplysninger om førstehjælp.

VED KONTAKT MED HUDEN: Vask med rigeligt vand (P302+P352)

3) I deklarationsfeltet:

a) Teksten ”Træbeskyttelsesmiddel BPR-reg. nr. 782-118-1. Aktivstof og biocidholdigt produkt er godkendt efter biociddirektivet (98/8/EF)”.

b) Oplysning om præparattype: ” væske” for dette præparat.

c) Indholdet af aktivstof i vægtprocent og g/L ved 20 °C.

d) Sætningen: ”Indeholder IPBC. Kan udløse allergisk reaktion (EUH208)”.

”Gentagen kontakt kan give tør eller revnet hud (EUH066)”.

e) Udløbsdatoen skal anføres. Denne dato må højst være 2 år efter produktionsdatoen. Etikettens dato kan udformes som en henvisning til en produktionsdato andetsteds på emballagen.

f) Batchnummer eller – betegnelse skal anføres.

g) Pakningsstørrelse i liter.

h) Godkendelsesindehavers navn og adresse.

4) Brugsanvisningen:

Oplysninger om skadevoldere, anvendelsesområde og doseringer.

Følgende retningslinjer gælder i forhold til bortskaffelse.

Der skal mærkes med sikkerhedssætning P501: ”Indholdet/holderen bortskaffes i overensstemmelse med kommunale regler for affaldshåndtering.”

Derudover skal mærkningen ske efter følgende retningslinjer:

Rester og tom emballage bortskaffes i henhold til de kommunale affaldsregulativer.