

EN

ANNEX

SUMMARY OF PRODUCT CHARACTERISTICS FOR A BIOCIDAL PRODUCT

Vacsol Aqua 6118

Product type(s)

PT08: Wood preservatives

Authorisation number: 5851

R4BP asset number: SE-0025059-0000

1. ADMINISTRATIVE INFORMATION

1.1. Trade name(s) of the product

Trade name(s)	Vacsol Aqua 6118 Tanalith MF
---------------	---------------------------------

1.2. Authorisation holder

Name and address of the authorisation holder	Name	YOU Solutions Germany GmbH
	Address	Seligmannallee 1 DE 30173 Hannover Germany
Authorisation number	5851	
<i>R4BP asset number</i>	SE-0025059-0000	
Date of the authorisation	04/11/2020	
Expiry date of the authorisation	02/11/2030	

1.3. Manufacturer(s) of the product

Name of manufacturer	Arch Timber Protection Ltd (A Lonza company)
Address of manufacturer	Wheldon Road WF10 2JT Castleford United Kingdom of Great Britain and Northern Ireland (the)
Location of manufacturing sites	Arch Timber Protection Ltd (A Lonza company) site 1 Leeds Road HD2 1YU Huddersfield United Kingdom of Great Britain and Northern Ireland (the)

1.4. Manufacturer(s) of the active substance(s)

Active substance	Penflufen
Name of manufacturer	LANXESS Deutschland GmbH
Address of manufacturer	Kennedyplatz 1 D-56569 Koln Germany
Location of manufacturing sites	LANXESS Deutschland GmbH site 1 Bayer AG, Alte Heerstr 41538 Dormagen Germany

Active substance	Permethrin
Name of manufacturer	Tagros Chemicals India Limited
Address of manufacturer	Jhaver Center, IV floor, Rajah Annamalai Building No . 72, Marshalls Road, Egmore 600 008 Chennai India
Location of manufacturing sites	Tagros Chemicals India Limited site 1 Tagros Chemicals India Limited A4/1&2 Sipcot Industrial Complex, Pachayankuppam, 607 005 Cuddalore, Tamil Nadu India

Active substance	Permethrin
Name of manufacturer	LANXESS Deutschland GmbH
Address of manufacturer	Kennedyplatz 1 D-56569 Koln Germany

Location of manufacturing sites

LANXESS Deutschland GmbH site 1 Bayer Vapi
Private Limited, Plot # 306/3 II Phase, GIDC, Vapi
396 195 Vapi, Gujarat India

2. PRODUCT COMPOSITION AND FORMULATION

2.1. Qualitative and quantitative information on the composition of the product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
Penflufen		active substance	494793-67-8		0,38 % (w/w)
Permethrin		active substance	52645-53-1	258-067-9	0,4 % (w/w)
Dimethyl myristyl amine, distilled; [N,N-dimethyl-C12-16-(even numbered)-alkyl-1-amines	Dimethyl myristyl amine, distilled; [N,N-dimethyl-C12-16-(even numbered)-alkyl-1-amines	Non-Active substance	68439-70-3	270-414-6	4,8 % (w/w)
Diethylene glycol monophenyl ether	2-(2-Phenoxyethoxy)ethanol	Non-Active substance	104-68-7	203-227-5	1,92 % (w/w)
Ethoxylated isodecanol		Non-Active substance	69011-36-5	500-241-6	3 % (w/w)
2-Phenoxyethanol	2-Phenoxyethanol	Non-Active substance	122-99-6	204-589-7	3,84 % (w/w)

2.2. Type(s) of formulation

SL Soluble concentrate

3. HAZARD AND PRECAUTIONARY STATEMENTS

Hazard statements	H315: Causes skin irritation. H318: Causes serious eye damage. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects. EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
Precautionary statements	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P264: Wash hands and skin thoroughly after handling. P280: Wear hands and skin. P280: Wear protective gloves. P280: Wear protective clothing. P280: Wear eye protection. P302+P352: IF ON SKIN: Wash with plenty of face protection. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER. P332+P313: If skin irritation occurs: Get medical POISON CENTER. P362+P364: Take off contaminated clothing and wash it before reuse. P391: Collect spillage. P501: Dispose of contents to approved waste disposal plant. P273: Avoid release to the environment.

4. AUTHORISED USE(S)

4.1. Use description

Table 1. Industrial preventative treatment

Product type	PT08: Wood preservatives
Where relevant, an exact description of the authorised use	Fungicide Insecticide
Target organism(s) (including development stage)	Scientific name: <i>Hylotrupes bajulus</i> L. Common name: house longhorn beetle Development stage: larvae Scientific name: Basidiomycetes: Basidiomycetes: Common name: brown rot fungi Development stage: hyphae
Field(s) of use	indoor use Indoor application of the wood preservative. Vacsol Aqua 6118 is a preventative wood preservative treatment against larvae of the house longhorn beetle (<i>Hylotrupes bajulus</i>) and brown rot fungi. The intended uses for Vacsol Aqua 6118 are applications of: Double vacuum and vacuum pressure application- Preventative treatment of wood and constructional timbers (all categories) in Use Classes 1, 2 & 3 and Dipping- Deluge/Enclosed Spray - Preventative treatment of wood and constructional timbers (all categories) in Use Classes 1 & 2 The product can be applied to both softwood and hardwood. Use Class 1 (situation in which the wood or wood-based product is inside a construction, not exposed to the weather and wetting). Use Class 2 (situation in which the wood or wood-based product is under cover and fully protected from the weather but occasional, non-persistent, wetting may occur. This can include outdoor placement of timber under a roof to prevent any exposure to rain and driven rain). Use Class 3 (situation in which the wood or wood-based product is not covered and not in contact with the ground. It is either continuously exposed to weather or protected from the weather but subject to frequent wetting).
Application method(s)	Method: closed system: vacuum impregnation Detailed description: Vacuum pressure Impregnation (High pressure) Method: closed system Detailed description: Double vacuum (Low pressure) Method: open system: dip treatment Detailed description: Industrial dipping Method: spraying Detailed description: Deluge / Enclosed spray
Application rate(s) and frequency	Application rate: Vacuum pressure (high pressure): 3.7 – 4.65 kg m ⁻³ Dilution (%): Dilution 0.62 to 1.25 Number and timing of application:

	<p>One application before timber is placed into service.</p> <p>Application rate: Dubble vacuum (low pressure): 3.7 – 4.65 kg m-3.</p> <p>Dilution (%): Dilution 1.50 to 5</p> <p>Number and timing of application: One application before timber is placed into service.</p> <p>Application rate: Industrial dipping: 10 g m-2</p> <p>Dilution (%): Dilution 10</p> <p>Number and timing of application: One application before timber is placed into service.</p> <p>Application rate: Spraying: 10 g m-2</p> <p>Dilution (%): Dilution: 10-20</p> <p>Number and timing of application: One application before timber is placed into service.</p>
Category(ies) of users	industrial
Pack sizes and packaging material	<ol style="list-style-type: none"> 1. HDPE IBC (1000 L) 2. HDPE IBC (640L) 3. HDPE Poly Keg (25L)

4.1.1. Use-specific instructions

see General directions for use

4.1.2. Use-specific risk mitigation measures

see General directions for use

4.1.3. Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see General directions for use

4.1.4. Where specific to the use, the instructions for safe disposal of the product and its packaging

see General directions for use

4.1.5. Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see General directions for use

5. GENERAL DIRECTIONS FOR USE¹

5.1. Instructions for use

For industrial use only.

For the prevention of brown rot fungi and larvae of *Hylotrupes bajulus* (House longhorn beetle):

- The product is supplied as a concentrate to be applied to timber by vacuum pressure, double vacuum, dipping or enclosed deluge spray systems after dilution with water.
 - Application processes must be carried out within a contained area situated on impermeable hard standing, with bunding to prevent run-off and a recovery system in place (e.g. sump).
 - The IBC containing the Vacsol Aqua 6118 is connected via a bottom locking run off valve directly to the treatment plant system. With the aid of automatic dosage equipment, concentrate is pumped from the IBC to the mixing tank or storage tank, along with the exact amount of water needed to make the relevant volume of treatment solution. The storage tank is topped up as required.
 - For double vacuum and vacuum pressure treatment, the diluted ready to use product is pumped into the impregnation cylinder to carry out the desired treatment.
 - For enclosed deluge systems the diluted ready to use product is applied in an enclosed chamber by means of flow coat or automatic spraying. Timber enters and exits the system on a conveyor with no manual handling.
 - Dipping is conducted only in industrial dip plants with no manual dipping, ie all wood is mechanically handled during the process.
- The Product should be diluted with water and applied at a retention rate as follows: Expressed as kg m⁻³ as concentrate in the analytical zone.
- An anti-foam (the applicant recommends the use of the anti-foaming agent 'Antifoam 1478'.) will be required for double-vacuum, high pressure and spray applications. It may not be required for dipping. A silicon antifoam (the applicant recommends the use of the anti-foaming agent 'Antifoam 1478'.) should be used at between 0.005-0.025% (depending on the solution strength).

Double vacuum (Low pressure)

Dilute to 1.5 - 5%:

-Use class 1, 2 and 3, retentions: 3.7 – 4.65 kg m⁻³.

Vacuum pressure (High pressure)

Dilute to 0.62 - 1.25%.

-Use class 3, retentions: 3.70 – 4.65 kg m⁻³.

Dipping

Dilute to 10%.

-Use class 1 and 2, retentions: 10 g m⁻²

Deluge/ Enclosed Spray

Dilute to 10 - 20%

-Use class 1 and 2, retentions: 10 g m⁻²

Freshly treated timber should be placed on an impermeable hard standing with bunding to prevent run-off that could contaminate ground, waterbodies or watercourses. Any run off from treated timber should be recovered.

¹Instructions for use, risk mitigation measures and other directions for use under this section are valid for any authorised uses.

5.2. Risk mitigation measures

All vacuum-pressure impregnation, double-vacuum, dipping and deluge treatment must only be undertaken at industrial sites where:

- Application processes are carried out within a contained area; situated on impermeable hard standing, with bunding to prevent run-off and a recovery system in place (e.g. sump).
- Application solutions must be collected and reused or disposed of as hazardous waste. They must not be released to soil, ground- and surface water or any kind of sewer.
- Do not apply near bodies of surface water or in the area of water protection zones. [where relevant provide for appropriate distance stipulations]
- Freshly treated timber shall be stored after treatment under shelter AND on impermeable hard standing to prevent losses to soil, sewer, or water, and that any losses from the application of the product shall be collected for reuse or disposal.
- Treated timber must not be placed over/near surface water bodies

The following phrases must appear on the label:

- Wear protective chemical resistant gloves* (glove material to be specified by the authorisation holder within the product information). *new gloves must be worn at the start of each treatment cycle
- A protective coverall (at least type X, EN XXXXX) which is impermeable for the biocidal product shall be worn (coverall material to be specified by the authorisation holder within the product information)
- The use of eye protection during handling of the product is mandatory

The following PPE requirements are appropriate for industrial users for the different types of treatment of Vacsol Aqua 6118:

- Automated dipping - impermeable coveralls and new gloves every cycle
- Deluge / enclosed spray treatment - coated coveralls and new gloves every cycle
- Double vacuum pressure treatment - coated coveralls and new gloves every cycle
- Vacuum pressure treatment - gloves

5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

IF INHALED: If symptoms occur call a POISON CENTRE or a doctor.

IF SWALLOWED: Immediately rinse mouth. Give something to drink, if exposed person is able to swallow. Do NOT induce vomiting. Call 112/ambulance for medical assistance.

IF ON SKIN: Take off all contaminated clothing and wash it before reuse. Wash skin with soap and water. If skin irritation or rash occur: Get medical advice.

IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Call 112/ambulance for medical assistance.

N-11: Application solutions must be collected and reused or disposed of as hazardous waste. They must not be released to soil, ground- and surface water or any kind of sewer.

N-13: All industrial application processes must be carried out within a contained area situated on impermeable hard standing with bunding to prevent run-off and a recovery system in place (e.g. sump).

N-19: Freshly treated timber must be stored after treatment under shelter or on impermeable hard standing, or both, to prevent direct losses to soil, sewer or water and that any losses of the product shall be collected for reuse or disposal.

N-21: Do not apply near bodies of surface water or in the area of water protection zones. [where relevant provide for appropriate distance stipulations].

5.4. Instructions for safe disposal of the product and its packaging

Rinse empty container with water and reuse water in treatment process.

Container's (IBC's) should be returned to the supplier for recycling. If this is not possible the container should be disposed of via an authorised waste disposal company in accordance with national legislation.

5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

Shelf life of 2 years

Store away from light

6. OTHER INFORMATION

Through their customer service activities and in their literature for treated wood, the authorization holder should inform about the restrictions of the treated wood, i.e. that the product should **not** be used:

- for treatment of timber placed over/near surface water bodies

The mixture contains 2,06% components with unknown acute oral toxicity, 26,75% components with unknown acute inhalation toxicity and 19,27% components with unknown acute dermal toxicity.

Content of the substances of concern (SoC), worst case:

Dimethyl myristyl amine, distilled; [N,N-dimethyl-C12-16-(even numbered)-alkyl-1-amines: < 4.80 %

Diethylene glycol monophenyl ether: < 1.92 %

Ethoxylated iso-tridecanol: < 3.00 %

2-Phenoxyethanol: < 3.84 %